

## Nätansluten Rökvarnare

MODEL		GARANTI
<b>ACX11BB</b>	Alkalisk batteribackup (3xAAA)	<b>5 ÅR</b>
<b>ACX11RB</b>	Uppladdningsbart litiumbatteri	<b>5 ÅR</b>

- **FAST FIX** monteringsplatta
- **RF-LINK KOMPATIBEL** utrustad med Radiomodulen (FHN600RF). Säljs separat.
- **TSE TEKNOLOGI** för snabb detektering
- för snabb detektering
- Test/paus med fjärrkontroll tillgänglig
- Låg energiförbrukning (< 0,5 W i standby-läge)



Radio Module  
(FHN600RF)  
kompatibel



1008-CPR-MC  
69266079 002

TEKNISK SPECIFIKATION	
Matningsspänning	230V ~ – 50Hz.
Reservkraft	ACX11BB – Batteribackup - 3 x AAA-batterier ACX11RB – Förseglat uppladdningsbart litiumbatteri-backup
Larmtyp	Nätansluten optisk rökdetektor
Larmförbindelse (tråd och/eller radio)	Trådbunden sammankoppling eller blandad radiosammankoppling vid montering med Radiomodulen (FHN600RF).
Larmåtgärd	Lågprofilsbas med "Fast-Fix"-funktion eller med reläbas FHN600
Test/Paus	Stor test-/pausknapp, Firehawk FHN600 Remote fjärrkontroll finns också tillgänglig.
Dimensioner	11.3cm (113mm) diameter x 5.5cm (55mm) Djup
Vikt	ACX11BB 196g / ACX11RB 168g
Larmljudnivå	85dB(A) vid 3m
Använd i:	Hall, vardagsrum, matsal, sovrum. Använd inte i kök (använd värmelarm)
Platser för installation	Tak eller vägg
Driftstemperatur	0°C – 40°C
Fuktighet vid drift	< 85% RH
Plastmaterial	ABS-klassad som V-0 enligt UL94
Förpackning	Separat låda och ytterkartong – återvinningsbar kartong.
Huvudförpackning/Ytterkartong	10 st
Max antal anslutna larm	15 via kabel eller 20 via trådlösa/RF-larm
Godkännande/Certifierad enligt	EN14604:2005 + AC:2008
Streckkod	ACX11BB – EAN 7332211103229 ACX11RB – EAN 7332211103243
Garanti	5 år (exklusive AAA-batterier)

**Deltronic Security AB, EA Rosengrensgata 4, 421 31 Västra Frölunda, Sverige**

Tel: 031-140800 | [order@deltronic.se](mailto:order@deltronic.se) | [www.deltronic.se](http://www.deltronic.se)

Deltronic reserve the right to change the design or specification details without prior notice.

# Mains Powered Optical Smoke Alarm

MODEL		WARRANTY
<b>ACX11BB</b>	Alkaline Battery Back-up (3xAAA)	<b>5 YEARS</b>
<b>ACX11RB</b>	Rechargeable Lithium Cell Back-up	<b>5 YEARS</b>

- **FAST FIX** mounting base
- **RF-LINK COMPATIBLE** when fitted with the RF-LINK module (FHN600RF). Sold separately.
- **TSE TECHNOLOGY** for fast detection
- Large test/silence button
- Remote control test/silence available
- Low energy usage (< 0.5W in standby mode)



RF-Link Radio Module (FHN600RF) compatible



1008-CPR-MC  
69266079 002

TECHNICAL SPECIFICATION	
Supply Voltage	230V ~ – 50Hz.
Back-Up Power	ACX11BB – Battery back-up -3 x AAA batteries ACX11RB – Sealed rechargeable lithium battery back up
Alarm Type	Mains Powered Optical Smoke Alarm
Alarm interlink (Wired or RF-Link)	Wired interconnect or mix radio interconnect when fitted with the RF-LINK module (FHN600RF).
Alarm Fixing	Low profile 'Fast-Fix' base or with Relay Base FHN600
Test/Hush	Large Test/Hush button, Firehawk FHN600REMOTE control also available.
Dimensions	11.3cm (113mm) diameter x 5.5cm (55mm) Depth
Weight	ACX11BB 196g / ACX11RB 168g
Alarm Sound level	85dB(A) at 3m
Use in:	Landing, hall, living room, dining room, bedrooms. Do not use in kitchen (use Heat Alarm)
Installation positions	Ceiling or wall
Operating Temperature	0°C – 40°C
Operating Humidity	< 85% RH
Plastic material	ABS Rated at V-0 against UL94
Packaging	Individual box & outer carton – recyclable cardboard.
Master pack/Outer carton	10 units
Max. num. of connected alarms	15 by cable or 20 by Wireless/RF alarms
Approval/Certified to	EN14604:2005 + AC:2008
Barcode	ACX11BB – EAN 7332211103229 ACX11RB – EAN 7332211103243
Warranty	5 years (excluding AAA batteries)

**Deltronic Security AB, EA Rosengrensgata 4, 421 31 Västra Frölunda, Sweden**

Tel: +46-31-140800 | [order@deltronic.se](mailto:order@deltronic.se) | [www.deltronic.se](http://www.deltronic.se)

Deltronic reserve the right to change the design or specification details without prior notice.